




# Balfit<sup>®</sup> Hydraulic Hose Fittings

## NON SKIVE Balfit<sup>®</sup> SAE 100R1AT / R2AT / R16 / R17 DIN EN 853 1SN / 2SN / DIN EN 857 1SC / 2SC Ferrule

*non-skive carbon steel ferrule for crimping on high pressure hydraulic hoses*

**Material:** carbon steel, zinc plated

**Connectors:** Balfit<sup>®</sup> crimped fittings 23 serie



### 20.204 - Ferrule for SAE 100R1AT / R2AT / R17 / DIN EN 853 1SN / 2SN / DIN EN 857 1SC / 2SC 2-MAX Hoses

part number	hose dash	hose Ø		dimensions (mm)	
		mm	inch	L	D
20.204.03	- 3	4,8	3/16"	26	21
20.204.04	- 4	6,3	1/4"	28,1	22
20.204.05	- 5	8,0	5/16"	28	24
20.204.06	- 6	9,5	3/8"	28,1	26
20.204.08	- 8	12,7	1/2"	31	30
20.204.10	- 10	16,0	5/8"	31	33
20.204.12	- 12	19,0	3/4"	31,5	37
20.204.16	- 16	25,4	1"	39,9	46
20.204.20	- 20	32,0	1-1/4"	44	58
20.204.24	- 24	38,0	1-1/2"	60,3	65
20.204.32	- 32	50,8	2"	62,7	78

also available:

### Balfit<sup>®</sup> Stainless Steel NON SKIVE Ferrules

(add an 'S' at the end of the part number; ex: 20.204.08S)

**Construction characteristics and dimensions may be changed at any time without prior notice.**

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex<sup>®</sup> – The European Technology**