


# Balfit® Hydraulic Spiral Hose Fittings



## Balfit® Spiral 90° Swept SUPERCAT Flange - 24.7196

*solid-piece, carbon steel Supercat 90° swept flanged fitting for crimping on high pressure hydraulic hoses*



According to **ISO 6162** and **ISO 12151-3** According to **SAE J516** and **SAE J518**

**Material :** carbon steel, zinc plated

**Ferrules :** Balfit® ferrules series 20.400 and 20.403

**Hoses :** Balflex® Balmaster hoses **SAE 100R9R / SAE 100R12 / DIN EN 856 4SP**  
may be also used on Balflex® Powerspir DIN EN 856 4SH hoses with Balfit ferrules series 20.403

part number	hose dash	hose Ø	Flange size	flange dash	D	C	E
		inch	inch		Ø Flange	Cut Off	
		mm	mm			mm	mm
24.7196.1212	- 12	3/4"	3/4"	- 12	41,3	56	60
24.7196.1216	- 12	3/4"	1"	- 16	47,6	56	67
24.7196.1616	- 16	1"	1"	- 16	47,6	71	79
24.7196.1620	- 16	1"	1.1/4"	- 20	54,0	72	85
23.7196.2020 *	- 20	1.1/4"	1.1/4"	- 20	54,0	85	90
23.7196.2024 *	- 20	1.1/4"	1.1/2"	- 24	63,5	91	92
23.7196.2424 *	- 24	1.1/2"	1.1/2"	- 24	63,5	99	104
23.7196.2432 *	- 24	1.1/2"	2"	- 32	79,4	99	112
23.7196.3232 *	- 32	2"	2"	- 32	79,4	125	136

\* On 1.1/4", 1.1/2" and 2" apply 23.7196

**Construction characteristics and dimensions may be changed at any time without prior notice.**

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex® – The European Technology**