




Balfit[®] Hydraulic Powerspir Hose Fittings

Balfit[®] Powerspir / Interlock JIC 37° Swivel Female - 26.4012

INTERNAL and EXTERNAL SKIVING carbon steel, JIC American thread, 37° flared female for crimping on very high pressure hydraulic hoses



According to **ISO 12151-5** and **ISO 8434-2** According to **SAE J516 / SAE J514**

- Material** : carbon steel, zinc plated
(Ferrule 20.405) Hoses : **Balflex[®] Powerspir** multi-spiral hoses **DIN EN 856 4SH Hose** (1.1/4", 1.1/2" and 2")
(Ferrule 20.406) Hoses : **Balflex[®] Powerspir** multi-spiral hoses **DIN EN 856 4SH Hose** (3/4" and 1"),
SAE 100R13 Hose (all sizes) and **SAE 100R15 Hose** (all sizes)

part number	hose dash	hose Ø	thread	thread dash	C Cut Off	Hex.
		inch				
26.4012.1212	- 12	3/4"	1-1/16" - 12	- 12	21	32
26.4012.1616	- 16	1"	1-5/16" - 12	- 16	23	41
26.4012.2020	- 20	1-1/4"	1-5/8" - 12	- 20	26	50
26.4012.2424	- 24	1-1/2"	1-7/8" - 12	- 24	27	55
26.4012.3232	- 32	2"	2-1/2" - 12	- 32	27	70

also available:

Balfit[®] Stainless Steel Powerspir JIC Female

(add an 'S' at the end of the part number; ex: 26.4012.0808 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology