


Balfit® Multicrimp Hydraulic Hose Fitting



Balfit® JIC 37° Swivel Female – P23.4012 one piece - non-skive

one-piece carbon steel, JIC American thread, 37° flared (5/8" - 18 is 45° flared) female for crimping on high pressure hydraulic hoses



According to **ISO 12151-5** and **ISO 8434-2** According to **SAE J516 / SAE J514**
(see option P23.4H12.- for back hexagon)

Material : one-piece one-piece carbon steel, zinc plated

Hoses : **Balflex®** wire braid hydraulic hoses **SAE 100R1AT / SAE 100R2AT / DIN EN 853 1SN / 2SN**
Balflex® 2 – MAX JACK

Balflex® Balpac compact hydraulic hoses **SAE 100R16 / SAE 100R17 / DIN EN 857 1SC / 2SC**

| part number | hose dash | hose | thread | thread dash | C Cut Off | Hex. |
|---------------|-----------|--------|--------------|-------------|--------------|------|
| | | Ø | | | | |
| | | inch | | | mm | mm |
| P23.4012.0304 | - 3 | 3/16" | 7/16" – 20 | - 4 | 13 | 15 |
| P23.4012.0404 | - 4 | 1/4" | 7/16" – 20 | - 4 | 15 | 15 |
| P23.4012.0405 | - 4 | 1/4" | 1/2" – 20 | - 5 | 15 | 17 |
| P23.4012.0406 | - 4 | 1/4" | 9/16" – 18 | - 6 | 15 | 19 |
| P23.4012.0506 | - 5 | 5/16" | 9/16" – 18 | - 6 | 16 | 19 |
| P23.4012.0606 | - 6 | 3/8" | 9/16" – 18 | - 6 | 16 | 19 |
| P23.4012.0607 | - 6 | 3/8" | 5/8" – 18 | - 7 | 15 | 22 |
| P23.4012.0608 | - 6 | 3/8" | 3/4" – 16 | - 8 | 18 | 24 |
| P23.4012.0610 | - 6 | 3/8" | 7/8" – 14 | - 10 | 19 | 27 |
| P23.4012.0808 | - 8 | 1/2" | 3/4" – 16 | - 8 | 18 | 24 |
| P23.4012.0810 | - 8 | 1/2" | 7/8" – 14 | - 10 | 19 | 27 |
| P23.4012.0812 | - 8 | 1/2" | 1.1/16" – 12 | - 12 | 21 | 32 |
| P23.4012.1010 | - 10 | 5/8" | 7/8" – 14 | - 10 | 20 | 27 |
| P23.4012.1012 | - 10 | 5/8" | 1.1/16" – 12 | - 12 | 21 | 32 |
| P23.4012.1212 | - 12 | 3/4" | 1.1/16" – 12 | - 12 | 21 | 32 |
| P23.4012.1214 | - 12 | 3/4" | 1.3/16" – 12 | - 14 | 21 | 36 |
| P23.4012.1216 | - 12 | 3/4" | 1.5/16" – 12 | - 16 | 22 | 41 |
| P23.4012.1616 | - 16 | 1" | 1.5/16" – 12 | - 16 | 23 | 41 |
| P23.4012.1620 | - 16 | 1" | 1.5/8" – 12 | - 20 | 25 | 50 |
| P23.4012.2020 | - 20 | 1.1/4" | 1.5/8" – 12 | - 20 | 26 | 50 |
| P23.4012.2424 | - 24 | 1.1/2" | 1.7/8" – 12 | - 24 | 27 | 55 |
| P23.4012.3232 | - 32 | 2" | 2.1/2" – 12 | - 32 | 27 | 70 |

also available:

Balfit® Multicrimp Stainless Steel JIC Female

(add an 'S' at the end of the part number; ex: P23.4012.0808 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology