


Balfit® Multicrimp Hydraulic Hose Fitting

Balfit[®] Metric French 90° Swept Female - P23.5593 one piece - non-skive

one piece carbon steel, metric (French metric thread, 24° cone) 90° Swept female fitting for crimping on high pressure hydraulic hoses



Material: carbon steel, zinc plated

Hoses: Balflex® wire braid hydraulic hoses SAE 100R1AT / SAE 100R2AT / DIN EN 853 1SN / 2SN

Balflex® 2 - MAX JACK

Balflex® Balpac compact hydraulic hoses SAE 100R16 / SAE 100R17 / DIN EN 857 1SC / 2SC

part number	hose dash	hose Ø	thread	thread dash	d - tube	C Cut Off	E	Hex.
		inch			mm	mm	mm	mm
P23.5593.0520	- 5	5/16"	M20 x 1,5	- 20	13,25	29	35	24
P23.5593.0620	- 6	3/8"	M20 x 1,5	- 20	13,25	34	32	24
P23.5593.0824	- 8	1/2"	M24 x 1,5	- 24	16,75	42	37	30
P23.5593.1030	- 10	5/8"	M30 x 1,5	- 30	21,25	46	46	36
P23.5593.1236	- 12	3/4"	M36 x 1,5	- 36	26,75	58	51	46

also available:

Balfit® Multicrimp Stainless Steel Metric 90° Swept French Female

(add an 'S' at the end of the part number; ex: P23.5593.0620 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology