


# Balflex® BALPAC DIN EN 1SC



## Balflex® BALPAC DIN EN 857 1SC – 10.1017. / 10.1018.

According to ISO 11237 –1 Norm type 1SC / DIN EN 857 Norm type 1SC

### High pressure, single steel braid reinforced hydraulic hose



- Inner tube:** seamless oil resistant synthetic rubber
- Reinforcement:** 1 high tensile steel wire braid
- Outer tube:** black, oil, weather and abrasion resistant synthetic rubber
- Safety factor:** 4 : 1
- Application:** petroleum base hydraulic fluids
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)  
Max. temperature recommended for water base hydraulic fluids: + 70°C (+ 158°F)  
Max. temperature recommended for air: + 60°C (+ 140°F)
- Couplings:** Balflex® crimped fittings series 23 with ferrules series 20

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
<b>10.1017.</b>													
10.1017.04	1/4"	- 4	6,3	0.25	12,7	0.50	22.5	3260	90.0	13040	51	2.0	0.22
10.1017.05	5/16"	- 5	8,0	0.31	15,0	0.59	21.0	3000	84.0	12000	60	2.4	0,27
10.1017.06	3/8"	- 6	9,5	0.38	16,5	0.65	21.0	3000	84.0	12000	64	2.5	0.34
10.1017.08	1/2"	- 8	12,7	0.50	20,8	0.82	21.0	3000	84.0	12000	89	3.5	0.42
<b>10.1018.</b>													
10.1018.10	5/8"	- 10	15,9	0.63	23.0	0.90	13.0	1885	52.0	7540	102	4.0	0.51
10.1018.12	3/4"	- 12	19,0	0.75	26.7	1.05	10.5	1523	42.0	6090	122	4.8	0.63
10.1018.16	1"	- 16	25,4	1.00	34.9	1.37	8.8	1276	35.2	5104	152	6.0	1.00

COVER: U.S. MSHA APPROVED

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex® – The European Technology**