




Balfit[®] Multicrimp Spiral Hose Fittings

Balfit[®] Multicrimp Spiral NPT Male P24.0400 / P12.0400 - one piece - non-skive

one piece carbon steel, NPT (dry-seal taper thread) male fitting for crimping on high pressure hydraulic hoses



According to **SAE J516 / SAE J514**

Material : carbon steel, zinc plated

P24 Series for Hoses : **Balflex[®] Balmaster** hoses **SAE 100R9R / DIN EN 856 4SP**

Balflex[®] Balmaster hose **SAE 100R12 (1/2" to 1")**

P12 Series for Hoses : **Balflex[®] Balmaster** hose **SAE 100R12 (1.1/4" to 2")**

part number	hose dash	hose Ø	thread	thread dash		C Cut Off	Hex.
		inch				mm	mm
P24.0400.0808	- 8	1/2"	1/2" – 14	- 8		35	22
P24.0400.1212	- 12	3/4"	3/4" – 14	- 12		39	27
P24.0400.1616	- 16	1"	1" – 11.5	- 16		45	36
P24.0400.2020	- 20	1.1/4"	1.1/4" – 11.5	- 20		49	46
P24.0400.2424	- 24	1.1/2"	1.1/2" – 11.5	- 24		51	50
P24.0400.3232	- 32	2"	2" – 11.5	- 32		55	65

part number	hose dash	hose Ø	thread	thread dash		C Cut Off	Hex.
		inch				mm	mm
P12.0400.2020	- 20	1.1/4"	1.1/4" – 11.5	- 20		49	46
P12.0400.2424	- 24	1.1/2"	1.1/2" – 11.5	- 24		51	50
P12.0400.3232	- 32	2"	2" – 11.5	- 32		55	65

also available:

Balfit[®] Stainless Steel Multicrimp Spiral NPT Male

(add an 'S' at the end of the part number; ex: P24.0400.0808 S or P12.0400.2020 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology