




# Balfit<sup>®</sup> Multicrimp R5 Hose Fittings

## Balfit<sup>®</sup> NPT Male – P25.0400 – one piece

one piece, carbon steel, NPT (dry-seal taper thread) male fitting for crimping on high pressure hydraulic hoses



According to **SAE J516 / SAE J514**

Material : carbon steel, zinc plated

Hoses : **Balflex<sup>®</sup>** wire braid hydraulic hose **SAE 100R5 / SAE J 1402 All**

part number	hose dash	hose Ø	thread	thread dash		C Cut Off	Hex.
		inch				mm	mm
P25.0400.0402	- 4	3/16"	1/8" – 27	- 2		22	12
P25.0400.0404	- 4	3/16"	1/4" – 18	- 4		28	17
P25.0400.0502	- 5	1/4"	1/8" – 27	- 2		23	12
P25.0400.0504	- 5	1/4"	1/4" – 18	- 4		28	17
P25.0400.0604	- 6	5/16"	1/4" – 18	- 4		28	17
P25.0400.0606	- 6	5/16"	3/8" – 18	- 6		28	19
P25.0400.0806	- 8	13/32"	3/8" – 18	- 6		30	19
P25.0400.0808	- 8	13/32"	1/2" – 14	- 8		35	22
P25.0400.1008	- 10	1/2"	1/2" – 14	- 8		35	22
P25.0400.1212	- 12	5/8"	3/4" – 14	- 12		38	27
P25.0400.1616	- 16	7/8"	1" – 11.5	- 16		44	36
P25.0400.2020	- 20	1.1/8"	1.1/4" – 11.5	- 20		50	46
P25.0400.2424	- 24	1.3/8"	1.1/2" – 11.5	- 24		51	50
P25.0400.3232	- 32	1.13/16"	2" – 11.5	- 32		55	65

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex<sup>®</sup> – The European Technology**