


Balflex® POWERSPIR SAE 100R13



Balflex® POWERSPIR SAE 100R13 – 5000PSI – 10.1009. * - 10.1014.

According to ISO 3862 / EN 856 type R13 / SAE J517 type R13

Very high pressure, four or six steel wire spirals reinforced hydraulic hose



- Inner tube:** seamless oil resistant synthetic rubber
- Reinforcement:** 4 or 6 spirals of high tensile steel wire
- Outer tube:** black, oil, weather and abrasion resistant synthetic rubber
- Safety factor:** 4: 1
- Application:** petroleum base hydraulic fluids
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)
Max. temperature recommended for water base hydraulic fluids: + 70°C (+ 158°F)
Max. temperature recommended for air: + 60°C (+ 140°F)
- Couplings:** Balflex® crimped fittings series 26 with ferrules 20.406 serie

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1009.12 *	3/4"	- 12	19,0	0.75	33,0	1.30	42.0	6090	168.0	24360	280	11.0	1,56
10.1009.16 *	1"	- 16	25,4	1.00	38,7	1.52	38.0	5510	152.0	22040	340	13.4	2,09
10.1014.20	1.1/4"	- 20	32,0	1.25	49,8	1.96	34.5	5000	138.0	20000	420	16.5	3,90
10.1014.24	1.1/2"	- 24	38,0	1.50	57,4	2.26	34.5	5000	138.0	20000	500	20.0	4,96
10.1014.32	2"	- 32	50,8	2.00	71,1	2.80	34.5	5000	138.0	20000	635	25.0	7,09

Note: According to ISO 3862 / EN 856 type R13 / SAE J517 type R13, the Balflex® POWERSPIR SAE 100R13 hose is of 4 steel wire spirals on sizes – 12 (3/4") and – 16 (1") and of 6 steel wire spirals on sizes – 20 (1.1/4"), – 24 (1.1/2") and – 32 (2").

* On sizes – 12 (3/4") and – 16 (1") the Balflex® POWERSPIR DIN EN 856 4SH and SAE 100R13 hoses are the same. The working pressure of Balflex® POWERSPIR DIN EN 856 4SH SAE 100R13 3/4" and Balflex® POWERSPIR DIN EN 856 4SH SAE 100R13 1" are higher than standard SAE 100R13.

COVER: U.S. MSHA APPROVED

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology