


Balfit[®] Hydraulic Adapters



Balfit[®] Male BSP x Male NPT Connector – 52.101

carbon steel straight union BSP 60° cone male x NPT male




According to **ISO 8434-6**

Material: Carbon Steel, zinc plated

part number	working pressure	thread		L	H
	bar	R1	R2	mm	mm
52.101.04	350	1/4" – 19	1/4" – 19	26	14
52.101.06	250	3/8" – 19	3/8" – 19	29	19
52.101.08	225	1/2" – 14	1/2" – 14	34	22
52.101.12	200	3/4" – 14	3/4" – 14	41	27
52.101.16	160	1" – 11	1" – 11	45	33
52.101.20	160	1-1/4" – 11	1-1/4" – 11	52	41
52.101.24	160	1-1/2" – 11	1-1/2" – 11	59	48
52.101.32	100	2" – 11	2" – 11	78	65

Balfit[®] 90° Male BSP x Male NPT Connector – 53.102

(90° carbon steel union BSP 60° cone male x NPT male)



According to **ISO 8434-6**

Material: Carbon Steel, zinc plated

part number	working pressure	thread		L	H
	bar	R1	R2	mm	mm
53.102.0404	350	1/4" – 19	1/4" – 19	26	14
53.102.0606	250	3/8" – 19	3/8" – 19	29	19
53.102.0808	225	1/2" – 14	1/2" – 14	34	22
53.102.1212	200	3/4" – 14	3/4" – 14	41	27
53.102.1616	160	1" – 11	1" – 11	45	33
53.102.2020	160	1-1/4" – 11	1-1/4" – 11	52	41
53.102.2424	160	1-1/2" – 11	1-1/2" – 11	59	48
53.102.3232	100	2" – 11	2" – 11	78	65

also available:

Balfit[®] Stainless Steel Male BSP x Male NPT / 90° Male BSP x Male NPT

(add an 'S' at the end of the part number; ex: 52.101.24 S - 53.102.1212 S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology