



## Balflex® EN 855 R7 / SAE 100R7 NON CONDUCTIVE TWIN – 10.1034.L

According to ISO 3949 / EN 855 type R7 / SAE J517 type SAE 100R7

**High pressure, synthetic fiber braid reinforced thermoplastic NON CONDUCTIVE hydraulic twin line hose**



- Inner tube:** seamless oil resistant thermoplastic
- Reinforcement:** 1 high tensile polyester braid
- Outer tube:** orange, oil and weather resistant polyurethane
- Safety factor:** 4: 1
- Application:** petroleum base hydraulic fluids
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F)  
Max. temperature recommended for water base hydraulic fluids: + 65°C (+ 149°F)
- Couplings:** Balflex® crimped fittings 23 serie with ferrules 20.107. serie

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1034.03L	3/16"	- 3	4,8	0.19	10,3	0.41	21.0	3045	84.0	12180	75	2.95	0,07
10.1034.04L	1/4"	- 4	6,3	0.25	12,4	0.49	19.0	2755	76.0	11020	100	3.94	0,09
10.1034.05L	5/16"	- 5	8,0	0.31	14,2	0.56	19.0	2755	76.0	11020	114	4.49	0,13
10.1034.06L	3/8"	- 6	9,5	0.38	15,7	0.62	16.0	2320	64.0	9280	127	5.00	0,16
10.1034.08L	1/2"	- 8	12,7	0.50	19,3	0.76	14.0	2030	56.0	8120	178	7.00	0,22
10.1034.10L	5/8"	- 10	16,0	0.63	23,1	0.91	10.5	1523	42.0	6092	203	7.99	0,28
10.1034.12L	3/4"	- 12	19,0	0.75	26,4	1.04	9.0	1305	36.0	5220	254	10.00	0,33
10.1034.16L	1"	- 16	25,4	1.00	33,3	1.31	7.0	1015	28.0	4060	305	12.00	0,40

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.