




Balflex® Hydraulic Quick Couplings


Balflex® AGRI Quick-Action Couplings (ball valve)

quick-action coupling for high pressure hydraulic systems with ball valve closure detail and female threaded connections

AGRICULTURAL QUICK COUPLING



40.A013 / 40.A003 - Male



40.A014 / 40.A004 - Female



Materials : carbon steel body, zinc plated, with synthetic rubber sealing rings and PTFE holding rings

Threads : female NPT or BSP

Valve closure detail : ball valve

Maximum operating temperature : + 98°C / + 208°F (other materials for higher temperatures as special features)

Minimum operating temperature : - 20°C / - 4°F (other materials for lower temperatures as special features)

Application : agricultural machinery

part number male	part number female	threaded connection	working pressure		dimensions (mm)						
			bar	PSI	B	H1	L1	C	D	H2	L2

with NPT thread

40.A013.08	40.A014.08	1/2" NPT	300	4350	21	30	58	24	38	30	74
------------	------------	----------	-----	------	----	----	----	----	----	----	----

with BSP thread

40.A003.08	40.A004.08	1/2" BSP	300	4350	21	30	58	24	38	30	74
------------	------------	----------	-----	------	----	----	----	----	----	----	----

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology