



Balflex® SAE 100R4 – 10.1219.

According to SAE J517 type SAE 100R4

Suction & Delivery hydraulic hose



- Inner tube:** seamless oil resistant synthetic rubber
- Reinforcement:** textile braids and 1 high strength steel wire helix
- Outer tube:** black, oil, weather and abrasion resistant synthetic rubber
- Safety factor:** 4: 1
- Application:** suction, delivery, return & discharge of petroleum base hydraulic fluids
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)
Max. temperature recommended for water base hydraulic fluids: + 70°C (+ 158°F)
Max. temperature recommended for air: + 60°C (+ 140°F)
- Couplings:** Balflex® fittings 23 serie up to 2" and 44 serie from 3" up to 4" with clamps

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
10.1219.12	3/4"	- 12	19,0	0.75	34,9	1.38	2.1	315	8.4	1260	127	5.0	0,75
10.1219.16	1"	- 16	25,4	1.00	41,3	1.63	1.7	255	6.8	1020	152	6.0	0,93
10.1219.20	1.1/4"	- 20	31,8	1.25	50,8	2.00	1.4	210	5.6	840	203	8.0	1,25
10.1219.24	1.1/2"	- 24	38,1	1.50	57,2	2.25	1.05	157.5	4.2	630	254	10.0	1,54
10.1219.32	2"	- 32	50,8	2.00	69,9	2.75	0.7	105	2.8	420	305	12.0	2,00
10.1219.40	2.1/2"	- 40	63,5	2.50	82,6	3.25	0.4	60	1.6	240	356	14.0	2,50
10.1219.48	3"	- 48	76,2	3.00	95,3	3.75	0.4	60	1.6	240	457	18.0	3,20
10.1219.56	3.1/2"	- 56	88,9	3.50	108	4.25	0.3	45	1.2	180	533	21.0	4,03
10.1219.64	4"	- 64	101,6	4.00	121	4.75	0.25	37.5	1.0	150	610	24.0	5,04

COVER: U.S. MSHA APPROVED

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.