

# Balflex® DIN EN 853 2SN / SAE 100R2AT

### Balflex® DIN EN 853 2SN / SAE 100R2AT SMOOTH COVER – 10.10S4.

According to ISO 1436 / DIN EN 853 type 2SN / SAE J517 type SAE 100R2 AT

## **SMOOTH COVER**

#### High pressure, smooth cover, double steel braid reinforced hydraulic hose



Inner tube: seamless oil resistant synthetic rubber

Reinforcement: 2 high tensile steel wire braids

Outer tube: black, oil, weather and abrasion smooth resistant synthetic rubber

Safety factor: 4: 1

Application: petroleum base hydraulic fluids

Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)

Max. temperature recommended for water base hydraulic fluids: + 70°C (+ 158°F)

Max. temperature recommended for air: + 60°C (+ 140°F)

Couplings: Balflex® crimped fittings 23 serie with ferrules 20 serie. Multicrimp P23 serie

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
10.10\$4.04	1/4"	- 4	6,3	0.25	15,0	0.59	40.0	5800	160.0	23200	100	3.9	0,38
10.10\$4.05	5/16"	- 5	8,0	0.31	16,6	0.65	35.0	5075	140.0	20300	114	4.5	0,45
10.10\$4.06	3/8"	- 6	9,5	0.38	19,0	0.75	33.0	4785	132.0	19140	127	5.0	0,53
10.10\$4.08	1/2"	- 8	12,7	0.50	22,2	0.87	27.5	3985	110.0	15940	178	7.0	0,65
10.10\$4.10	5/8"	- 10	16,0	0.63	25,5	1.00	25.0	3625	100.0	14500	200	7.9	0,76
10.10S4.12	3/4"	- 12	19,0	0.75	29,4	1.15	21.5	3120	86.0	12480	240	9.4	1,00
10.10S4.16	1"	- 16	25,4	1.00	37,9	1.50	16.5	2390	65.0	9560	300	11.8	1,48

Note: usually not available in stock, only by order.

Balflex® hydraulic hose DIN EN 853 2SN / SAE 100R2AT has a very superior working and burst pressure compared with only SAE 100R2AT

COVER: U.S. MSHA APPROVED

#### Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

(I) HYDR-2010 - **40** © Balflex 2010