


Balflex® AIRMASTER Air & Water 300PSI



Balflex® AIRMASTER AIR & WATER – 10.1232.

Exceeds ISO 2398 / BS 5118 type 2

Air & Water 2.0MPa / 300PSI (100% rubber hose)



- Inner tube:** seamless air and water resistant synthetic rubber
- Reinforcement:** 1 high resistance synthetic fiber braid
- Outer tube:** black, weather and abrasion resistant synthetic rubber
- Safety factor:** 3: 1
- Application:** heavy works on mining, construction, steel plants, quarries and air compressors
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1232.04	1/4"	- 4	6,0	0.24	14,0	0.55	2.0	300	6.0	900	60	2.4	0,17
10.1232.05	5/16"	- 5	8,0	0.32	17,0	0.67	2.0	300	6.0	900	80	3.2	0,22
10.1232.06	3/8"	- 6	10,0	0.39	19,0	0.75	2.0	300	6.0	900	100	3.9	0,26
10.1232.08	1/2"	- 8	13,0	0.51	21,0	0.83	2.0	300	6.0	900	125	4.9	0,33
10.1232.10	5/8"	- 10	16,0	0.63	26,0	1.02	2.0	300	6.0	900	160	6.3	0,50
10.1232.12	3/4"	- 12	19,0	0.75	29,0	1.14	2.0	300	6.0	900	190	7.5	0,56
10.1232.16	1"	- 16	25,0	0.98	36,0	1.42	2.0	300	6.0	900	254	10.0	0,83

Balflex® AIRMASTER AIR & WATER **YELLOW** – 10.1232.Y

Exceeds ISO 2398 / BS 5118 type 2

Yellow Air & Water 2.0MPa / 300PSI (100% rubber hose)



- Inner tube:** seamless air and water resistant synthetic rubber
- Reinforcement:** 1 high resistance synthetic fiber braid
- Outer tube:** yellow, weather and abrasion resistant synthetic rubber
- Safety factor:** 3: 1
- Application:** heavy works on mining, construction, steel plants, quarries and air compressors
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1232.04Y	1/4"	- 4	6,0	0.24	14,0	0.55	2.0	300	6.0	900	60	2.4	0,17
10.1232.05Y	5/16"	- 5	8,0	0.32	17,0	0.67	2.0	300	6.0	900	80	3.2	0,22
10.1232.06Y	3/8"	- 6	10,0	0.39	19,0	0.75	2.0	300	6.0	900	100	3.9	0,26
10.1232.08Y	1/2"	- 8	13,0	0.51	21,0	0.83	2.0	300	6.0	900	125	4.9	0,33
10.1232.10Y	5/8"	- 10	16,0	0.63	26,0	1.02	2.0	300	6.0	900	160	6.3	0,50
10.1232.12Y	3/4"	- 12	19,0	0.75	29,0	1.14	2.0	300	6.0	900	190	7.5	0,56
10.1232.16Y	1"	- 16	25,0	0.98	36,0	1.42	2.0	300	6.0	900	254	10.0	0,83

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology