

Balflex® BALPAC PREMIUM SAE 100R16



Balflex® ARMORGUARD BALPAC PREMIUM SAE 100R16 – 10.1019.--A

According to **SAE J517 Norm type / SAE 100R16 / ISO 11237 –1 Norm type R16**

Balflex® ARMORGUARD VERY HIGH ABRASION RESISTANCE

Exceeds SAE 100R16

Very High pressure, double steel wire braid reinforced hydraulic hose



Inner tube: seamless oil resistant synthetic rubber

Reinforcement: 2 high tensile steel wire braids

Outer tube: black, oil, weather and VERY HIGH abrasion resistant synthetic rubber

Safety factor: 4: 1

Application: petroleum base hydraulic fluids

Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)

Max. temperature recommended for water base hydraulic fluids: **+ 70°C (+ 158°F)**

Max. temperature recommended for air: **+ 60°C (+ 140°F)**

Couplings: Balflex® crimped fittings 23 serie with ferrules 20 serie. Multicrimp P23 serie

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1019.04A	1/4"	- 4	6,3	0.25	13,3	0.52	40.0	5800	160.0	23200	50	2.0	0,27
10.1019.05A	5/16"	- 5	8,0	0.31	15,0	0.59	35.0	5075	140.0	20300	57	2,2	0,30
10.1019.06A	3/8"	- 6	9,5	0.38	17,1	0.67	33.0	4785	132.0	19140	65	2.6	0,42
10.1019.08A	1/2"	- 8	12,7	0.50	20,6	0.81	27.6	4000	110.4	16000	90	3.5	0,52
10.1019.10A	5/8"	- 10	16,0	0.63	23,7	0.93	25.0	3625	100.0	14500	100	3.9	0,63
10.1019.12A	3/4"	- 12	19,0	0.75	27,7	1.09	21.5	3118	86.0	12472	120	4.7	0,80
10.1019.16A	1"	- 16	25,4	1.00	35,8	1.41	16.5	2393	66.0	9572	150	5.9	1,22

COVER: U.S. MSHA APPROVED

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology