



Balflex® BALPAC PREMIUM DIN EN 2SC

Balflex® ARMORGUARD BALPAC PREMIUM DIN EN 857 2SC 10.1019.--A

According to ISO 11237 -1 Norm type 2SC / DIN EN 857 Norm type 2SC

Balflex® ARMORGUARD VERY HIGH ABRASION RESISTANCE

High pressure, double steel braid reinforced hydraulic hose



- Inner tube :** seamless oil resistant synthetic rubber
- Reinforcement :** 2 high tensile steel wire braid
- Outer tube :** black, oil, weather and VERY HIGH abrasion resistant synthetic rubber
- Safety factor :** 4 : 1
- Application :** petroleum base hydraulic fluids
- Temperature range :** - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)
Max. temperature recommended for water base hydraulic fluids: + 70°C (+ 158°F)
Max. temperature recommended for air: + 60°C (+ 140°F)
- Couplings :** Balflex® crimped fittings series 23 with ferrules series 20

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1019.04A	1/4"	- 4	6,3	0.25	13,3	0.52	40.0	5800	160.0	23200	50	2.0	0.27
10.1019.05A	5/16"	- 5	8,0	0.31	15,0	0.59	35.0	5075	140.0	20300	57	2.2	0.30
10.1019.06A	3/8"	- 6	9,5	0.38	17,1	0.67	33.0	4785	132.0	19140	65	2.6	0.42
10.1019.08A	1/2"	- 8	12,7	0.50	20,6	0.81	27.6	4000	110.4	16000	90	3.5	0.52
10.1019.10A	5/8"	- 10	15,9	0.63	23,7	0.93	25.0	3625	100.0	14500	100	3.9	0.63
10.1019.12A	3/4"	- 12	19,0	0.75	27,7	1.09	21.5	3118	86.0	12472	120	4.7	0.80
10.1019.16A	1"	- 16	25,4	1.00	35,8	1.41	16.5	2393	66.0	9572	150	5.9	1.22

COVER: U.S. MSHA APPROVED

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology