



Balflex® POWERSPIR SAE 100R15

Balflex® ARMORGUARD POWERSPIR SAE 100R15 – 6000PSI

10.1016.--A

According to **ISO 3862 / EN 856** type **R15** / **SAE J517** type **R15**

Balflex® ARMORGUARD VERY HIGH ABRASION RESISTANCE

Very high pressure, four or six steel wire spirals reinforced hydraulic hose



Inner tube: seamless oil resistant synthetic rubber

Reinforcement: 4 or 6 spirals of high tensile steel wire

Outer tube: black, oil, weather and VERY HIGH abrasion resistant synthetic rubber

Safety factor: 4: 1

Application: petroleum base hydraulic fluids

Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F); Intermittent service: + 120°C (+ 248°F)

Max. temperature recommended for water base hydraulic fluids: + 70°C (+ 158°F)

Max. temperature recommended for air: + 60°C (+ 140°F)

Couplings: Balflex® crimped fittings series 26 with ferrules 20 serie

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1016.06A	3/8"	- 6	9,5	0.38	23,3	0.92	42.0	6000	168.0	24000	153	6.0	0,75
10.1016.08A	1/2"	- 8	12,7	0.50	26,8	1.06	42.0	6000	168.0	24000	203	8.0	0,89
10.1009.12A*	3/4"	- 12	19,0	0.75	36,1	1.42	42.0	6000	168.0	24000	267	10.5	1,56
10.1016.16A	1"	- 16	25,4	1.00	42,9	1.69	42.0	6000	168.0	24000	330	13.0	2,10
10.1016.20A	1 1/4"	- 20	32,0	1.25	51,5	2.03	42.0	6000	168.0	24000	445	17.5	3,65
10.1016.24A	1 1/2"	- 24	38,0	1.50	59,6	2.32	42.0	6000	168.0	24000	533	21.0	5,00

Note: According to **ISO 3862 / EN 856** type **R15** / **SAE J517** type **R15**, the **Balflex® POWERSPIR SAE 100R15** hose is of 4 steel wire spirals on sizes – 6 (3/8"), 8 (1/2"), – 12 (3/4") and – 16 (1") and of 6 steel wire spirals on sizes – 20 (1.1/4") and – 24 (1.1/2").

According to **ISO 3862 / SAE J517** type **R15** doesn't exist the size – 32 (2").

* On size – 12 (3/4") the **Balflex® POWERSPIR DIN EN 856 4SH** and **SAE 100R15** hoses are the same

COVER: U.S. MSHA APPROVED

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.