




Balflex® WASHSTEAM – 10.1120.

Saturated Steam synthetic textile braid hose + 165°C (+ 330°F)

0.7 MPa / 102PSI W.P. - 7.0 Mpa / 1015PSI B.P.



- Inner tube:** black, heat resistance synthetic rubber
- Reinforcement:** high tensile synthetic textile braids
- Outer tube:** white heat, weather and abrasion resistant synthetic rubber
- Safety factor:** 10: 1
- Application:** for general saturated steam services. Food plants
- Temperature range:** - 40°C (- 40°F) + 165°C (+ 330°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
10.1120.06	3/8"	- 6	9,5	0.38	17,0	0.67	0.7	102	7.0	1015	68	2.68	0.33
10.1120.08	1/2"	- 8	12,7	0.50	22,0	0.87	0.7	102	7.0	1015	80	3.15	0.39
10.1120.12	3/4"	- 12	19,0	0.75	32,0	1.26	0.7	102	7.0	1015	135	5.31	0.67
10.1120.16	1"	- 16	25,4	1.00	38,0	1.50	0.7	102	7.0	1015	170	6.69	0.83
10.1120.20	1.1/4"	- 20	31,8	1.25	45,0	1.77	0.7	102	7.0	1015	240	9.45	1.10
10.1120.24	1.1/2"	- 24	38,1	1.50	51,0	2.01	0.7	102	7.0	1015	300	11.81	1.27
10.1120.32	2"	- 32	50,8	2.00	66,0	2.60	0.7	102	7.0	1015	375	14.76	1.83

Smooth cover on sizes – 6 and – 8, wrapped cover on sizes – 12, - 16, - 20, - 24, - 32.

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.