


Balflex® STEEL WIRE CONCRETE



Balflex® STEEL WIRE REINFORCED CONCRETE – 10.1247.

Hose for Placement of Concrete to the Casting Locations

Abrasion loss value: Acc DIN 53516 < 65 mm³



- Inner tube:** seamless special synthetic rubber resistant to abrasion
- Reinforcement:** high tensile steel cords
- Outer tube:** black, weather and abrasion resistant pin-pricked synthetic rubber
- Safety factor:** 2.3: 1
- Application:** placement of concrete to the casting locations
- Temperature range:** - 40°C (- 40°F) + 70°C (+ 158°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1247.050	2"	- 32	50,8	2.00	70,0	2.76	8.5	1232	20	2900	510	20.1	3,41
10.1247.063	2.1/2"	- 40	63,5	2.50	88,0	3.46	8.5	1232	20	2900	635	25.0	4,97
10.1247.075	3"	- 48	76,0	3.00	102,0	4,02	8.5	1232	20	2900	762	30.0	6,58
10.1247.100	4"	- 64	101,0	3.98	130,0	5,12	8.5	1232	20	2900	1016	40.0	9,38
10.1247.125	5"	- 80	127,0	5.00	155,0	6,10	8.5	1232	20	2900	1270	50.0	10,95
101247.150	6"	- 96	152,0	5.98	184,0	7,24	8.5	1232	20	2900	1524	60.0	13,49

Can be supplied already assembly, with fittings, upon request

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology