



Balflex® PAINT SPRAY – 10.1042.

Paint Spray hose 1 or 2 aramidic braids



- Inner tube:** internal core in polyamide
- Reinforcement:** 1 or 2 high tensile aramidic braid with antistatic polymeric braid
- Outer tube:** blue pin pricked polyurethane high abrasion resistance
- Safety factor:** 4: 1
- Application:** high pressure airless spray systems, chemical resistance to solvents and aggressive fluids
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F) max. temperature recommended for water base hydraulic fluids and air: **+ 70°C (+ 158°F)**
- Couplings:** crimped **Balflex® PaintSpray** coupling serie

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1042.03	3/16"	- 3	4,8	0.19	10,3	0.41	35.0	5000	140.0	20000	50	2.0	0,09
10.1042.04	1/4"	- 4	6,3	0.25	12,4	0.49	35.0	5000	140.0	20000	75	3.0	0,10
10.1042.06	3/8"	- 6	9,5	0.38	15,7	0.62	30.0	4350	120.0	17400	100	4.0	0,18
10.1042.08	1/2"	- 8	12,7	0.50	19,3	0.76	24.5	3500	98.0	14000	120	4.7	0,22

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.