



Beverage Dispensing hose



Inner tube:	thermoplastic elastomer food quality
Reinforcement:	10.1034. with 1 synthetic fiber braid; 10.1044. with 1 steel braid; 10.1045. with 1 aramidic braid
Outer tube:	grey color pin pricked polyurethane
Safety factor:	4: 1
Application:	designed specially for CO ² gas mixtures used in fixed and mobile beverages dispensing units. Special tube material with flavour free that eliminates contamination risks
Temperature range:	- 40°C (- 40°F) + 80°C (+ 176°F)
Couplings:	crimped Balflex® fittings

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1043.04	1/4"	- 4	6,3	0.25	12,2	0.48	21.0	3000	84.0	12000	35	1.4	0,05
10.1044.03	3/16"	- 3	4,8	0.19	9,7	0.38	35.0	5000	140.0	20000	40	1.6	0,07
10.1044.04	1/4"	- 4	6,3	0.25	11,7	0.46	32.0	4650	128.0	18600	45	1.8	0,08
10.1045.02	1/8"	- 2	3,2	0.13	8,1	0.32	42.0	6000	168.0	24000	25	1.0	0,05
10.1045.03	3/16"	- 3	4,8	0.19	10,3	0.41	35.0	5000	140.0	20000	25	1.0	0,07
10.1045.04	1/4"	- 4	6,3	0.25	12,4	0.49	35.0	5000	140.0	20000	32	1.3	0,09

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.