



Mini Bore hose



Inner tube:	thermoplastic elastomer
Reinforcement:	10.1046. with 1 synthetic fiber braid; 10.1047. with 1 aramidic fiber braid
Outer tube:	black color polyurethane
Safety factor:	4: 1
Application:	designed specially for very high pressure mini hydraulic lines. Automotive and truck's cab lifting systems.
Temperature range:	- 40°C (- 40°F) + 100°C (+ 212°F)
Couplings:	crimped Balflex® fittings

part number	Ø nom	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
		mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
10.1046.03	1/8"	3,2	0.13	6,5	0.26	25.0	3600	100.0	14400	20	0.8	0.05
10.1047.02	5/64"	2,0	0.08	5,0	0.20	63.0	9100	189.0	27300	20	0.8	0.06
10.1047.03	1/8"	3,2	0.13	6,0	0.24	63.0	9100	189.0	27300	30	1.2	0.07
10.1047.04	5/32"	4,0	0.16	8,0	0.32	63.0	9100	189.0	27300	40	1.6	0.08

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.