



Balflex® BALSPRAY ELITE

Balflex® BALSPRAY ELITE 1160PSI – 12.1003.

Flexible Hose of PVC compound for High Pressure Agricultural Pulverization



- Inner tube :** PVC compound black, highly flexible, resistant to abrasion
- Internal surface :** smooth, passage facilitator
- Reinforcement :** 2 braids of high tensile synthetic yarn
- Outer tube :** PVC compound, resistant to ozone, UV rays and to abrasion
- Color :** black inner tube / orange outer tube
- Coil length :** 100 meters
- Safety factor :** 3 : 1
- Temperature range :** - 10°C (+14°F) + 55°C (+ 131°F)
- Application :** services of pulverization of insecticide, herbicides and pesticides

| part number | Ø nom. | dash size | Ø internal | Ø external | working pressure | | min. burst pressure | |
|-------------|--------|-----------|------------|------------|------------------|------|---------------------|------|
| | | | mm | mm | MPa | PSI | MPa | PSI |
| 12.1003.04 | 1/4" | - 4 | 6,4 ± 0,3 | 11,0 ± 0,3 | 8.0 | 1160 | 24.0 | 3480 |
| 12.1003.05 | 5/16" | - 5 | 7,9 ± 0,3 | 13,5 ± 0,3 | 8.0 | 1160 | 24.0 | 3480 |
| 12.1003.06 | 3/8" | - 6 | 9,5 ± 0,3 | 16,0 ± 0,3 | 8.0 | 1160 | 24.0 | 3480 |
| 12.1003.08 | 1/2" | - 8 | 12,7 ± 0,3 | 20,0 ± 0,3 | 8.0 | 1160 | 24.0 | 3480 |
| 12.1003.12 | 3/4" | - 12 | 19,1 ± 0,5 | 28,0 ± 0,4 | 8.0 | 1160 | 24.0 | 3480 |

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology