




Flexible Hose of PVC Reinforced with Steel Spiral



- Inner tube :** PVC, highly flexible, resistant to abrasion, weather and UV rays
- Internal surface :** smooth, passage facilitator
- Reinforcement :** 1 wire helix of galvanized steel of high resistance
- Color :** transparent crystal
- Safety factor :** 3 : 1
- Temperature range :** - 10°C (+14°F) + 55°C (+ 131°F)
- Application :** food industry, water pumps, agriculture, fiber impulsion

part number	Ø nom.	dash size	Ø internal	Ø external	min. burst pressure	vacuum	coils
			mm	mm	PSI	PSI	Mts
12.1227.012	1/2"	- 12	12,0	18,0 ± 2,0	100	7	100
12.1227.014	9/16"	- 14	14,0	20,0 ± 2,0	85	6	100
12.1227.016	5/8"	- 16	16,0	23,0 ± 2,0	85	6	100
12.1227.018	11/16"	- 18	18,0	25,0 ± 2,0	85	6	100
12.1227.020	3/4"	- 20	20,0	26,0 ± 2,0	70	5	50
12.1227.022	7/8"	- 22	22,0	28,0 ± 2,0	70	5	50
12.1227.025	1"	- 25	25,0	32,0 ± 2,0	70	5	50
12.1227.030	1.3/16"	- 30	30,0	38,0 ± 2,0	60	4	50
12.1227.032	1.1/4"	- 32	32,0	41,0 ± 2,0	60	4	50
12.1227.035	1.3/8"	- 35	35,0	44,0 ± 2,0	60	4	50
12.1227.038	1.1/2"	- 38	38,0	47,0 ± 2,0	60	4	50
12.1227.040	1.9/16"	- 40	40,0	49,0 ± 2,0	40	3	50
12.1227.045	1.3/4"	- 45	45,0	54,0 ± 2,0	40	3	50
12.1227.050	2"	- 50	50,0	59,0 ± 2,0	40	3	50
12.1227.060	2.3/8"	- 60	60,0	70,0 ± 2,0	29	2	20
12.1227.070	2.3/4"	- 70	70,0	81,0 ± 2,0	29	2	20
12.1227.076	3"	- 76	76,0	87,0 ± 2,0	20	2	20
12.1227.080	3.1/4"	- 80	80,0	91,0 ± 2,0	29	2	20
12.1227.090	3.1/2"	- 90	90,0	101,0 ± 2,0	29	2	10
12.1227.102	4"	- 102	102,0	113,0 ± 2,0	29	2	10

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.