


Balfit® ORFS Fittings



Balfit® Male Connector (ORFS x NPT) – 36.200.

carbon steel ORFS male x NPT (American taper thread) male connector



According to ISO 8434-3 According to SAE J1453

Material: Carbon Steel
Finish: Carbon Steel

part number	thread		dimensions			
	R1	R2	B	L1	L2	H
36.200.0402	9/16" – 18	1/8" – 27	27	10	9.7	17
36.200.0404	9/16" – 18	1/4" – 18	32	10	14.2	17
36.200.0406	9/16" – 18	3/8" – 18	33.5	10	14.2	19
36.200.0604	11/16" – 16	1/4" – 18	33	11	14.2	19
36.200.0606	11/16" – 16	3/8" – 18	34	11	14.2	19
36.200.0608	11/16" – 16	1/2" – 14	39.5	11	19	22
36.200.0806	13/16" – 16	3/8" – 18	37.5	13	14.2	22
36.200.0808	13/16" – 16	1/2" – 14	41.5	13	19	22
36.200.0812	13/16" – 16	3/4" – 14	43	13	19	27
36.200.1008	1" – 14	1/2" – 14	45.5	15.5	19	27
36.200.1012	1" – 14	3/4" – 14	45.5	15.5	19	27
36.200.1208	1.3/16" – 12	1/2" – 14	49	17	19	32
36.200.1212	1.3/16" – 12	3/4" – 14	49	17	19	32
36.200.1216	1.3/16" – 12	1" – 11 1/2"	54	17	23.9	36
36.200.1612	1.7/16" – 12	3/4" – 14	49.5	17.5	19	41
36.200.1616	1.7/16" – 12	1" – 11.1/2"	55.5	17.5	23.9	41
36.200.2020	1.11/16" – 12	1.1/4" – 11.1/2"	58	17.5	24.6	46
36.200.2424	1.7/8" – 12	1.1/2" – 11.1/2"	61	17.5	25.4	55

also available:

Balfit® Stainless Steel Male Connector

(add an 'S' at the end of the part number; ex: 36.200.0806S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology