




Balfit[®] Compression Ring Pipe Fittings

Balfit[®] 24° Compression Ring – 34.101.

double edged carbon steel compression ring for 24° compression ring pipe fittings



According to **ISO 8434-1** According to **DIN 2353**

Material: Carbon Steel

Finish: Heat treated, passivated and zinc-plated

part number	Ø tube	dimensions		working pressure	ISO series
	mm	L1	D	MPa	
34.101.06LS	6	9,5	10	31.5	L
34.101.08LS	8	9,5	12	31.5	L
34.101.10LS	10	10	14	31.5	L
34.101.12LS	12	10	16	31.5	L
34.101.15L	15	10	19	31.5	L
34.101.18L	18	10	23	31.5	L
34.101.22L	22	10,5	27	16.0	L
34.101.28L	28	11	33	16.0	L
34.101.35L	35	13	41	16.0	L
34.101.42L	42	13	48	16.0	L
34.101.14S	14	10	19	63.0	S
34.101.16S	16	10,5	21	40.0	S
34.101.20S	20	12	26	40.0	S
34.101.25S	25	12	32	40.0	S
34.101.30S	30	13	36	40.0	S
34.101.38S	38	13	44	31.5	S

also available:

Balfit[®] Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.101.15LS)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology