


Balfit® Compression Ring Pipe Fittings



Balfit® NPTF Taper Male Connector – 34.118.

carbon steel NPTF thread male stud 24° standpipe adapter



According to **ISO 8434-1** According to **DIN 2353**

Material: Carbon Steel
Finish: Zinc-plated

part number	Ø tube	thread	dimensions						working pressure	ISO series
			mm	G	L1	L2	L3	H1		
34.118.06LN02	6	1/8	31,5	17	10	12	14		31.5	L
34.118.08LN04	8	1/4	38	23	15	17	17		31.5	L
34.118.10LN04	10	1/4	39	24	15	17	19		31.5	L
34.118.12LN06	12	3/8	39,5	25	15	19	22		31.5	L
34.118.15LN08	15	1/2	46	31	19,5	24	27		31.5	L
34.118.18LN08	18	1/2	48	31,5	19,5	27	32		31.5	L
34.118.22LN12	22	3/4	50	33,5	20	32	36		16.0	L
34.118.28LN16	28	1	56	39,5	25	41	41		16.0	L
34.118.35LN20	35	1-1/4	62	40,5	25,5	46	50		16.0	L
34.118.42LN24	42	1-1/2	65	42	26	55	60		16.0	L
34.118.06SN04	6	1/4	41	26	15	17	17		63.0	S
34.118.08SN04	8	1/4	43	28	15	17	19		63.0	S
34.118.10SN06	10	3/8	43,5	27,5	15	19	22		63.0	S
34.118.12SN06	12	3/8	45,5	29,5	15	22	24		63.0	S
34.118.14SN08	14	1/2	54	36	19,5	24	27		63.0	S
34.118.16SN08	16	1/2	54	35,5	19,5	27	30		40.0	S
34.118.20SN12	20	3/4	59	37,5	20	32	36		40.0	S
34.118.25SN16	25	1	69	45	25	41	46		40.0	S
34.118.30SN20	30	1-1/4	73	46,5	25,5	46	50		40.0	S
34.118.38SN24	38	1-1/2	80	49	26	55	60		31.5	S
34.118.06LN04	6	1/4	37,5	23	15	14	14		31.5	L
34.118.08LN02	8	1/8	33	18	10	17	17		31.5	L

also available:

Balfit® Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.118.12SN06)

continued on next page

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology




Balfit[®] Compression Ring Pipe Fittings

continued

Balfit[®] NPTF Taper Male Connector – 34.118.

carbon steel NPTF thread male stud 24° standpipe adapter



According to **ISO 8434-1** According to **DIN 2353**

Material: Carbon Steel

Finish: Zinc-plated

part number	Ø tube	thread	dimensions						working pressure	ISO series
	mm	G	L1	L2	L3	H1	H2	MPa		
34.118.08LN06	8	3/8	39	24	15	19	17	31.5	L	
34.118.08LN08	8	1/2	44	29	19,5	22	17	31.5	L	
34.118.10LN02	10	1/8	34	19	10	17	19	31.5	L	
34.118.10LN06	10	3/8	40	25	15	19	19	31.5	L	
34.118.10LN08	10	1/2	45	30	19,5	22	19	31.5	L	
34.118.12LN04	12	1/4	39,5	25	15	19	22	31.5	L	
34.118.12LN08	12	1/2	44,5	30	19,5	22	22	31.5	L	
34.118.15LN06	15	3/8	41	26	15	24	27	31.5	L	
34.118.18LN12	18	3/4	48	31,5	20	32	32	31.5	L	
34.118.12SN08	12	1/2	50,5	34,5	19,5	24	24	63.0	S	
34.118.14SN06	14	3/8	49	31	15	24	27	63.0	S	
34.118.16SN06	16	3/8	49	30,5	15	27	30	40.0	S	
34.118.20SN08	20	1/2	59	37,5	19,5	32	36	40.0	S	
34.118.25SN12	25	3/4	64	40	20	41	46	40.0	S	
34.118.30SN16	30	1	72	45,5	25	46	50	40.0	S	

also available:

Balfit[®] Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.118.12SN08)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology