




Balfit[®] Compression Ring Pipe Fittings

Balfit[®] Straight Union – 34.135.

carbon steel straight 24° compression ring connector



According to **ISO 8434-1** According to **DIN 2353**

Material: Carbon Steel

Finish: Zinc-plated

part number	Ø tube	thread	dimensions						working pressure	ISO series
	mm	G	L1	L2	H1	H2		MPa		
34.135.06L	6		39	10	10	12		31.5	L	
34.135.08L	8		40	11	11	14		31.5	L	
34.135.10L	10		42	13	13	17		31.5	L	
34.135.12L	12		43	14	14	19		31.5	L	
34.135.15L	15		46	16	16	24		31.5	L	
34.135.18L	18		48	16	16	27		31.5	L	
34.135.22L	22		52	20	20	32		16.0	L	
34.135.28L	28		54	21	21	41		16.0	L	
34.135.35L	35		63	20	20	46		16.0	L	
34.135.42L	42		66	21	21	55		16.0	L	
34.135.06S	6		45	16	16	14		63.0	S	
34.135.08S	8		47	18	18	17		63.0	S	
34.135.10S	10		49	17	17	19		63.0	S	
34.135.12S	12		51	19	19	22		63.0	S	
34.135.14S	14		57	22	22	24		63.0	S	
34.135.16S	16		57	21	21	27		40.0	S	
34.135.20S	20		66	23	23	32		40.0	S	
34.135.25S	25		74	26	26	41		40.0	S	
34.135.30S	30		80	27	27	46		40.0	S	
34.135.38S	38		90	29	29	55		31.5	S	

also available:

Balfit[®] Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.135.12S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology