

# Balflex® BALDRILL MINE AIR & WATER



## Balflex® BALDRILL MINE AIR & WATER – 10.1233.

According to BS 5118-20

**Rigid rubber heavy mandrel hose for delivery of Air and Water 2.0MPa / 300PSI**

**Reinforced with several high resistance synthetic fiber braids**



- Inner tube:** seamless air and water resistant synthetic rubber
- Reinforcement:** several high resistance synthetic fiber braids
- Outer tube:** yellow, weather and abrasion resistant synthetic rubber
- Safety factor:** 3: 1
- Application:** heavy works on mining, construction, steel plants, perforation and quarries
- Temperature range:** - 35°C (- 31°F) + 85°C (+ 185°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1233.20	1.1/4"	- 20	31,8	1.25	43,0	1.69	2.0	300	6.0	900	320	12.6	1,17
10.1233.24	1.1/2"	- 24	38,1	1.50	50,0	1.97	2.0	300	6.0	900	380	15.0	1,33
10.1233.32	2"	- 32	50,8	2.00	64,0	2.52	2.0	300	6.0	900	510	20.1	1,96
10.1233.40	2.1/2"	- 40	63,5	2.50	77,0	3.03	2.0	300	6.0	900	635	25.0	2,90
10.1233.48	3"	- 48	76,2	3.00	90,0	3.54	2.0	300	6.0	900	762	30.0	3,57
10.1233.64	4"	- 64	101,6	4.00	118,0	4.65	2.0	300	6.0	900	1016	40.0	5,20

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex® – The European Technology**