




Balflex® OILTANK – 10.1238.

Rigid rubber mandrel TANK TRUCK hose for delivery of Petroleum, Gasoline, Oil and Fuel 1.0MPa / 150PSI

Reinforced with several high resistance synthetic fiber braids and antistatic copper line



Inner tube: synthetic rubber resistant to oil, gasoline, diesel and fuels with up to 40% aromatic content, with antistatic characteristics

Reinforcement: several high resistance synthetic fiber braids

Outer tube: black, oil, weather and abrasion resistant synthetic rubber, with antistatic copper line

Safety factor: 3: 1

Application: delivery of oil, gasoline, diesel and fuels

Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1238.025	1"	- 16	25,4	1.00	36,0	1.42	1.0	150	3.0	450	254	10.0	0,60
10.1238.032	1.1/4"	- 20	31,8	1.25	43,0	1.69	1.0	150	3.0	450	320	12.6	1,14
10.1238.040	1.1/2"	- 24	38,1	1.50	49,0	1.93	1.0	150	3.0	450	380	15.0	1,30
10.1238.050	2"	- 32	50,8	2.00	61,0	2.40	1.0	150	3.0	450	510	20.1	1,75
10.1238.063	2.1/2"	- 40	63,5	2.50	76,0	2.99	1.0	150	3.0	450	635	25.0	1,90
10.1238.075	3"	- 48	76,2	3.00	88,0	3.46	1.0	150	3.0	450	762	30.0	2,50
10.1238.090	3.1/2"	- 56	88,9	3.50	106,0	4,17	1.0	150	3.0	450	900	35.4	3,00
10.1238.100	4"	- 64	101,6	4.00	115,0	4.53	1.0	150	3.0	450	1016	40.0	3,60
10.1238.125	5"	- 80	127,0	5.00	140,0	5.51	1.0	150	3.0	450	1270	50.0	4,00
10.1238.150	6"	- 96	152,4	6.00	165,0	6.50	1.0	150	3.0	450	1524	60.0	4,60

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.