


Balfit® Compression Ring Pipe Fittings



Balfit® Welding Boss – 34.155.

carbon steel weld-on 24° compression ring standpipe connector



According to **ISO 8434-1** According to **DIN 2353**

Material: Carbon Steel
Finish: Zinc-plated

part number	Ø tube	thread	dimensions							working pressure	ISO series
	mm	P	L1	L2	L3	L4				MPa	
34.155.06L	6	10	29	14	12	14				31.5	L
34.155.08L	8	12	31	16	14	17				31.5	L
34.155.10L	10	14	33	18	17	19				31.5	L
34.155.12L	12	16	33	18	19	22				31.5	L
34.155.15L	15	19	37	22	22	27				31.5	L
34.155.18L	18	22	40	23,5	27	32				31.5	L
34.155.22L	22	27	45	28,5	32	36				16.0	L
34.155.28L	28	32	47	30,5	41	41				16.0	L
34.155.35L	35	40	54	32,5	46	50				16.0	L
34.155.42L	42	46	58	35	55	60				16.0	L
34.155.06S	6	11	34	19	14	17				63.0	S
34.155.08S	8	13	36	21	17	19				63.0	S
34.155.10S	10	15	39	22,5	19	22				63.0	S
34.155.12S	12	17	41	24,5	22	24				63.0	S
34.155.14S	14	19	45	27	24	27				63.0	S
34.155.16S	16	21	45	26,5	27	30				40.0	S
34.155.20S	20	26	51	29,5	32	36				40.0	S
34.155.25S	25	31	56	32	41	46				40.0	S
34.155.30S	30	36	62	35,5	46	50				40.0	S
34.155.38S	38	44	69	38	55	60				31.5	S

also available:

Balfit® Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.155.16S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology