



Balflex® RADIATOR – 10.1262.

Radiator Hose 0.4MPa / 60PSI



Inner tube: black EPDM resistant to hot water
Reinforcement: high tensile textile cords
Outer tube: black, heat, weather and abrasion resistant EPDM rubber
Safety factor: 3: 1
Application: vehicle radiator hose
Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F)

part number	Ø nom		Ø internal		Ø external		working pressure		min. burst pressure		weight
	inch	mm	inch	mm	inch	mm	MPa	PSI	MPa	PSI	
10.1262.020	3/4"	19,0	0.75	27,0	1.06	0.4	60	1.2	180	0,37	
10.1262.022	7/8"	22,0	0.87	29,0	1.14	0.4	60	1.2	180	0,41	
10.1262.025	1"	25,0	0.98	32,0	1.26	0.4	60	1.2	180	0,46	
10.1262.028	1.1/8"	28,0	1.10	36,0	1.42	0.4	60	1.2	180	0,51	
10.1262.032	1.1/4"	32,0	1.26	40,0	1.57	0.4	60	1.2	180	0,57	
10.1262.035	1.3/8"	35,0	1.38	43,0	1.69	0.4	60	1.2	180	0,62	
10.1262.038	1.1/2"	38,0	1.50	47,5	1.87	0.4	60	1.2	180	0,85	
10.1262.042	1.5/8"	42,0	1.65	51,0	2.01	0.4	60	1.2	180	0,92	
10.1262.045	1.3/4"	45,0	1.77	54,5	2.15	0.4	60	1.2	180	0,99	
10.1262.048	1.7/8"	48,0	1.90	57,0	2.24	0.4	60	1.2	180	1,03	
10.1262.050	2"	50,0	1.97	60,0	2.36	0.4	60	1.2	180	1,10	
10.1262.055	2.1/8"	55,0	2.17	65,0	2.56	0.4	60	1.2	180	1,19	
10.1262.057	2.1/4"	57,0	2.24	67,0	2.64	0.4	60	1.2	180	1,23	
10.1262.060	2.3/8"	60,0	2.36	70,0	2.76	0.4	60	1.2	180	1,28	
10.1262.063	2.1/2"	63,0	2.48	73,0	2.87	0.4	60	1.2	180	1,34	
10.1262.070	2.3/4"	70,0	2.76	80,0	3.15	0.4	60	1.2	180	1,51	
10.1262.075	3"	76,0	2.99	86,0	3.39	0.4	60	1.2	180	1,62	
10.1262.090	3.1/2"	90,0	3.54	102,0	4.02	0.4	60	1.2	180	1,95	
10.1262.100	4"	100,0	3.94	113,0	4.45	0.4	60	1.2	180	2,08	

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.