


Balfit[®] Compression Ring Pipe Fittings



Balfit[®] Metric Swivel Union – 34.635.

carbon steel parallel Metric thread 24° compression fitting swivel union



24° compression fitting according to **DIN 3865 form B**

Material: Carbon Steel

Finish: Zinc-plated

part number	Ø tube mm	dimensions							working pressure MPa	ISO series
		L1	H2				m	O-ring		
34.635.06L	6	37	14				12x1,5	4x1,5	31.5	L
34.635.08L	8	37	17				14x1,5	6x1,5	31.5	L
34.635.10L	10	38	19				16x1,5	7,5x1,5	31.5	L
34.635.12L	12	38	22				18x1,5	9x1,5	31.5	L
34.635.15L	15	42	27				22x1,5	12x2	31.5	L
34.635.18L	18	40	32				26x1,5	15x2	31.5	L
34.635.22L	22	47	36				30x2	20x2	16.0	L
34.635.28L	28	48	41				36x2	26x2	16.0	L
34.635.35L	35	56	50				45x2	32x2,5	16.0	L
34.635.42L	42	56	60				52x2	38x2,5	16.0	L
34.635.06S	6	38	17				14x1,5	4x1,5	63.0	S
34.635.08S	8	38	19				16x1,5	6x1,5	63.0	S
34.635.10S	10	41	22				18x1,5	7,5x1,5	63.0	S
34.635.12S	12	42	24				20x1,5	9x1,5	63.0	S
34.635.14S	14	45	27				22x1,5	10x2	63.0	S
34.635.16S	16	47	30				24x1,5	12x2	40.0	S
34.635.20S	20	55	36				30x2	16,3x2,4	40.0	S
34.635.25S	25	59	46				36x2	20,3x2,4	40.0	S
34.635.30S	30	62	50				42x2	25,3x2,4	40.0	S
34.635.38S	38	67	60				52x2	33,3x2,4	31.5	S

also available:

Balfit[®] Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.635.12S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex[®] – The European Technology