




Balflex® SUPERSTEAM – 10.1260.

Saturated Steam steel braid hose + 208°C (+ 406°F)

1.7 MPa / 250PSI W.P. 17.0 Mpa / 2500PSI B.P.



Inner tube: black, heat resistance synthetic rubber

Reinforcement: high tensile steel wire braids

Outer tube: black heat, weather and abrasion resistant synthetic rubber

Safety factor: 10: 1

Application: super heated steam services in chemical plants, steel mills, refineries, shipyards

Temperature range: - 40°C (- 40°F) + 208°C (+ 406°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
10.1260.08	1/2"	- 8	12,7	0.50	25,0	0.98	1.7	250	17.0	2500	180	7.1	0,55
10.1260.12	3/4"	- 12	19,0	0.75	31,0	1.22	1.7	250	17.0	2500	240	9.4	0,74
10.1260.16	1"	- 16	25,4	1.00	38,3	1.51	1.7	250	17.0	2500	300	11.8	0,97
10.1260.20	1.1/4"	- 20	31,8	1.25	46,5	1.83	1.7	250	17.0	2500	400	15.7	1,30
10.1260.24	1.1/2"	- 24	38,1	1.50	53,0	2.09	1.7	250	17.0	2500	500	19.7	1,65
10.1260.32	2"	- 32	50,8	2.00	67,0	2.64	1.7	250	17.0	2500	650	25.6	2,50

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.