




Balflex® DRY CEMENT DELIVERY – 10.1241.

According to EN ISO 3861 / ISO 4649

Dry bulk materials and dry powder cement delivery hose

Reinforced with several high resistance synthetic fiber braids with antistatic copper line



- Inner tube:** seamless synthetic rubber resistant to abrasion
- Reinforcement:** high tensile textile cords
- Outer tube:** black, weather and abrasion resistant synthetic rubber with antistatic copper line
- Safety factor:** 3: 1
- Application:** discharge of dry bulk materials, sand, gravel, and dry powder cement
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1241.050	2"	- 32	50,8	2.00	62,0	2.44	0.5	75	1.5	225	510	20.1	1,24
10.1241.063	2.1/2"	- 40	63,5	2.50	75,0	2.95	0.5	75	1.5	225	635	25.0	1,60
10.1241.075	3"	- 48	76,0	3.00	90,0	3.54	0.5	75	1.5	225	762	30.0	1,98
10.1241.090	3.1/2"	- 56	90,0	3.54	104,0	4.09	0.5	75	1.5	225	900	35.4	2,51
10.1241.100	4"	- 64	101,0	3.98	115,0	4.53	0.5	75	1.5	225	1016	40.0	3,18
10.1241.125	5"	- 80	127,0	5.00	140,0	5.51	0.5	75	1.5	225	1270	50.0	4,05
10.1241.150	6"	- 96	152,0	5.98	166,0	6.54	0.5	75	1.5	225	1524	60.0	5,05
10.1241.200	8"	- 128	203,0	7.99	218,0	8.58	0.5	75	1.5	225	2032	80.0	7,80

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.