



Balflex® Balwash 155°C 2W 400bar

Balflex® Balwash 155°C (+ 311°F) 400bar – 10.2WJ0.

High pressure, double wire braid reinforced high temperature car wash hose



- Inner tube:** seamless hot water resistant synthetic rubber
- Reinforcement:** 2 high tensile steel wire braid
- Outer tube:** black, oil, weather and abrasion pin-pricked resistant synthetic rubber
- Safety factor:** 4: 1
- Application:** high temperature and high pressure cleaning professional equipments
- Temperature range:** 0°C (+ 32°F) + 155°C (+ 311°F)
- Couplings:** Balflex® crimped fittings series 23 with ferrules series 20.

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	bar	PSI	bar	PSI	mm	inch	
10.2WJ0.04	1/4"	- 4	6,3	0.25	11,7	0.46	400	5800	1600	23200	100	3.9	0,38
10.2WJ0.05	5/16"	- 5	8,0	0.31	15,0	0.59	400	5800	1600	23200	110	4.4	0,45
10.2WJ0.06	3/8"	- 6	9,5	0.38	17,4	0.69	400	5800	1600	23200	120	4.8	0,53

Balflex® Balwash 155°C (+ 311°F) 400bar – 10.2WJB.

High pressure, blue, double wire braid reinforced high temperature car wash hose



- Inner tube:** seamless hot water resistant synthetic rubber
- Reinforcement:** 2 high tensile steel wire braid
- Outer tube:** blue, oil, weather and abrasion pin-pricked resistant synthetic rubber
- Safety factor:** 4: 1
- Application:** high temperature and high pressure cleaning professional equipments
- Temperature range:** 0°C (+ 32°F) + 155°C (+ 311°F)
- Couplings:** Balflex® crimped fittings series 23 with ferrules series 20.

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	bar	PSI	bar	PSI	mm	inch	
10.2WJB.05	5/16"	- 5	8,0	0.31	15,0	0.59	400	5800	1600	23200	110	4.4	0,45
10.2WJB.06	3/8"	- 6	9,5	0.38	17,4	0.69	400	5800	1600	23200	120	4.8	0,53

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology