




Extremely high pressure hose for Waterblasting



- Inner tube:** seamless synthetic rubber resistant to water at very high pressure
- Reinforcement:** 6 spirals of high tensile steel wire
- Outer tube:** black, oil, weather and abrasion resistant synthetic rubber
- Safety factor:** 2.5: 1
- Application:** very high pressure waterblasting
- Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F)
- Couplings:** crimped **Balflex® Waterblast** coupling serie

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
10.1024.04	1/4"	- 4	6,4	0.25	20,6	0.81	140.0	20300	355.0	51475	150	5.9	0.92
10.1024.06	3/8"	- 6	9,5	0.37	24,0	0.94	140.0	20300	355.0	51475	180	7.1	1.37
10.1024.08	1/2"	- 8	12,7	0.50	29,0	1.14	140.0	20300	365.0	52925	230	9.1	1.90

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.