



Sewer jet cleaning hose



- Inner tube:** internal core in poliester
- Reinforcement:** 2 high tensile aramidic fiber braids
- Outer tube:** orange polyurethane high abrasion resistance
- Safety factor:** 2.5: 1
- Application:** sewer cleaning with high pressure water
- Temperature range:** - 40°C (- 40°F) + 65°C (+ 149°F)
- Couplings:** crimped **Balflex® Jetclean** coupling serie

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
10.1039.08	1/2"	- 8	13,0	0.51	20,3	0.80	24.1	3500	60.3	8750	100	4.0	0,21
10.1039.10	5/8"	- 10	16,0	0.63	25,6	1.01	20.7	3000	51.7	7500	125	5.0	0,35
10.1039.12	3/4"	- 12	19,0	0.75	29,8	1.17	20.7	3000	51.8	7500	125	5.0	0,48
10.1039.16	1"	- 16	25,4	1.00	36,5	1.44	20.7	3000	51.8	7500	150	6.0	0,58

The **Balflex®** Sewer JETCLEAN hoses are supplied in lengths of 120 meters (393,7 feet) long

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.