



Balflex® AIRPRESSOR PT 300

Balflex® AIRPRESSOR AIR & WATER – 10.1234

Flexible Hose of PVC compound for Air & Water 300 PSI



- Inner tube :** black PVC compound, highly flexible, resistant to abrasion
- Internal surface :** smooth, passage facilitator
- Reinforcement :** 1 braid of high tensile synthetic yarn
- Outer tube :** black PVC compound, resistant to ozone, UV rays and to abrasion
- Coil lenght :** 50 / 100 meters
- Safety factor :** 3 : 1
- Temperature range :** - 10°C (+14°F) + 55°C (+ 131°F)
- Application :** industrial services of air and water, in compressors, pneumatic facilities, washing services and for water and air conduction

part number	Ø nom.	dash size	Ø internal		working pressure		min. burst pressure	
			mm	mm	MPa	PSI	MPa	PSI
10.1234.04	1/4"	- 4	6,4 ± 0,3	12,2	2.0	300	6.0	900
10.1234.05	5/16"	- 5	7,9 ± 0,3	14,0	2.0	300	6.0	900
10.1234.06	3/8"	- 6	9,5 ± 0,3	15,7	2.0	300	6.0	900
10.1234.08	1/2"	- 8	12,7 ± 0,3	18,0	2.0	300	6.0	900
10.1234.10	5/8"	- 10	15,8 ± 0,5	22,0	2.0	300	6.0	900
10.1234.12	3/4"	- 12	19,1 ± 0,5	25,5	2.0	300	6.0	900
10.1234.16	1"	- 16	25,4 ± 0,5	32,0	2.0	300	6.0	900

Balflex® AIRPRESSOR AIR & WATER RED – 10.1234.R

- Inner tube :** black PVC compound, highly flexible, resistant to abrasion
- Internal surface :** smooth, passage facilitator
- Reinforcement :** 1 braid of high tensile synthetic yarn
- Outer tube :** red PVC compound, resistant to ozone, UV rays and to abrasion
- Coil lenght :** 50 / 100 meters
- Safety factor :** 3 : 1
- Temperature range :** - 10°C (+14°F) + 55°C (+ 131°F)
- Application :** industrial services of air and water, in compressors, pneumatic facilities, washing services and for water and air conduction

part number	Ø nom.	dash size	Ø internal		working pressure		min. burst pressure	
			mm	mm	MPa	PSI	MPa	PSI
10.1234.04R	1/4"	- 4	6,4 ± 0,3	12,2	2.0	300	6.0	900
10.1234.05R	5/16"	- 5	7,9 ± 0,3	14,0	2.0	300	6.0	900
10.1234.06R	3/8"	- 6	9,5 ± 0,3	15,7	2.0	300	6.0	900
10.1234.08R	1/2"	- 8	12,7 ± 0,3	18,0	2.0	300	6.0	900
10.1234.10R	5/8"	- 10	15,8 ± 0,5	22,0	2.0	300	6.0	900
10.1234.12R	3/4"	- 12	19,1 ± 0,5	25,5	2.0	300	6.0	900
10.1234.16R	1"	- 16	25,4 ± 0,5	32,0	2.0	300	6.0	900

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology