

Balflex® BAL-L / Light Services S & D



Balflex® BAL – L SUCTION & DELIVERY – 12.9040.

Flexible Hose of PVC Reinforced with Spiral



- Inner tube :** PVC, highly flexible, resistant to abrasion, weather and UV rays
- Internal surface :** smooth, passage facilitator
- Reinforcement :** high resistant PVC spiral
- Color :** transparent crystal with blue spiral
- Coil lenght :** 25 / 50 meters (30 meters in 5"e 6')
- Safety factor :** 2.5 : 1
- Temperature range :** - 10°C (+14°F) + 55°C (+ 131°F)
- Application :** light services of water suction and discharge, agricultural irrigation, tank trucks, industrial water circuits and chemical products, gallery cleaning.

part number	Ø nom.	dash size	Ø internal	Ø external	working pressure	min. burst pressure	vacuum	coils
			mm	mm	PSI	PSI	PSI	Mts
12.9040.019	3/4"	- 19	19,0 ± 0,5	25,0 ± 1,0	120	300	15	25 / 50
12.9040.025	1"	- 25	25,0 ± 0,5	32,0 ± 1,0	108	270	15	25 / 50
12.9040.032	1.1/4"	- 32	32,0 ± 0,5	37,0 ± 1,0	96	240	15	25 / 50
12.9040.038	1.1/2"	- 38	38,0 ± 0,5	44,0 ± 1,0	96	240	15	25 / 50
12.9040.050	2"	- 50	50,0 ± 1,0	57,0 ± 1,0	96	240	15	25 / 50
12.9040.063	2.1/2"	- 63	62,0 ± 1,0	71,0 ± 1,5	90	225	15	25 / 50
12.9040.075	3"	- 75	75,0 ± 1,0	83,0 ± 1,5	84	210	15	25 / 50
12.9040.100	4"	- 100	100,0 ± 1,0	112,0 ± 1,5	78	195	15	25 / 50
12.9040.125	5"	- 125	127,0 ± 1,0	139,0 ± 1,5	72	180	15	30
12.9040.150	6"	- 150	152,0 ± 1,0	165,0 ± 1,5	66	165	15	30

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

Balflex® – The European Technology