

# Balflex® BAL-AP / Heavy Vacuum Suction



**Balflex® BAL – AP HEAVY VACUUM SUCTION – 12.9060.**

## Flexible Hose of PVC Reinforced with Spiral



- Inner tube :** PVC, highly flexible, resistant to abrasion e weather
- Internal surface :** smooth, passage facilitator
- External surface :** corrugated, allowing even more flexibility
- Reinforcement :** high resistant PVC spiral
- Color :** blue
- Coil lenght :** 25 / 50 meters (30 meters in 5" and 6')
- Safety factor :** 2.5 : 1
- Temperature range :** - 10°C (+14°F) + 55°C (+ 131°F)
- Application :** suction and industrial exhaust, for example, in wood mills and textile industry. Superior resistance to friction of the particles in suspension.

part number	Ø nom.	dash size	Ø internal	Ø external	vacuum	coils
			mm	mm		
12.9060.025	1"	25	25,0 ± 0,5	29,5 ± 1,0	8	25 / 50
12.9060.032	1.1/4"	32	32,0 ± 0,5	37,5 ± 1,0	8	25 / 50
12.9060.038	1.1/2"	38	38,0 ± 0,5	44,0 ± 1,0	8	25 / 50
12.9060.050	2"	50	50,0 ± 1,0	57,0 ± 1,0	8	25 / 50
12.9060.063	2.1/2"	63	62,0 ± 1,0	72,0 ± 1,5	7	25 / 50
12.9060.075	3"	75	75,0 ± 1,0	84,0 ± 1,5	7	25 / 50
12.9060.100	4"	100	100,0 ± 1,0	111,0 ± 1,5	6	25 / 50
12.9060.125	5"	125	127,0 ± 1,0	139,0 ± 1,5	5	30
12.9060.150	6"	150	152,0 ± 1,0	164,0 ± 1,5	4	30

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex® – The European Technology**